CONFIGURATION

Model	1325-ATC	1530-ATC	2030-ATC	2040-ATC
Working Area	1300*2500mm	1500*3000mm	2000*3000mm	2000*4000mm
Tool Magazine	Automatic Linear tool change (Carousel Tool Magazine)			
Tool Holder Quantity	4/6/8/10			
Spindle Power	HQD 9kw ATC air-cooled Spindle			
Spindle Speed	0-24000RPM			
Tool Setting	Automatic Tool Height calibration sensor			
Tool Cooling	Oil-mist Spray Assembly (optional)			
Working Table	Multi-zone vacuum with T-slot table with gate valves for zone control			
Control System	XDW203C Controller(Handle Control)/NK280/Taiwan Syntec Industrial Control System			
Drive&Motor	Delta 750W servo motor (Japan YASKAWA 850W)			
Reducer	Japanese high precision gear reduction			
XY Structure	1.5M precision helical rack,Taiwan brand linear guide rail			
Z Structure	Z-axis adopts aviation aluminum alloy T6061/6063, Taiwan TBI ball screws			
Lubrication System	Auto lubration system for rack gear and ball screws			
Alignment Tools	Pneumatic Piston Reference Pins(optional)			
Other Function	CCD/Oscillating Knife/Creasing Tool/Rotary Axis			
Gross Power	22KW			
Power Consumption	22kWh/h			
Repeat Positioning Accuracy	±0.01mm			

Working Voltage	220V/380V
Operating Software	VCarve, Artcam, Ucancam, Aspire,CorelDraw, Type3,SolidWorks, Artcut, AutoCAD,etc.
Language Command	G Code