

CONFIGURATION

| Model | ZPRO | | | |
|--------------------------|---|-------------|-------------|-------------|
| Working Area | 1300*2500mm | 1500*3000mm | 2000*3000mm | 2000*4000mm |
| Machine Function | ATC Spindle+CCD camera+150W Oscillating knife cutting head (Optional creasing tool) | | | |
| Tool Magazine | Concealed Linear Tool Magazine | | | |
| Tool Holder Quantity | ISO20 Tool Holder*8 | | | |
| Repositioning Resolution | ±0.01mm | | | |
| XY-axis Transmission | 40 tooth-1.5M / H50 gear rack,25mm guide rail | | | |
| Z-axis Transmission | TBI-SFU2505 ball screw&disc coupling,20mm guide rail | | | |
| Spindle Power&Speed | 4KW water-cooled spindle&40000RPM | | | |
| Drive Motors | LeadShine 750W servo motor and driver | | | |
| Reducer | Japan SHIMPO reducer structure 1:10 | | | |
| Operating System | VC-204C PC version control system | | | |
| Lubrication System | Auto lubration system for sliders and guide rails | | | |
| Gross Power | 16KW | | | |
| Power Consumption | 16kwh/h | | | |
| Working Table | Vacuum&T-slot table,5.5kw vacuum pump | | | |
| Tool Setting | High precision auto tool calibrator | | | |