

CONFIGURATION

COMMODITY	TRADE TERMS (LCL)	QUANTITY (SET)	TOTALAMOUNT (USD)
SESAME S2			
CONFIGURATION	Working area	1300*2500*200mm	
	Control System	XINGDUOWEI HD100 handle controller	
	Spindle	4.5kw UTECH air cooled spindle	
	Spindle speed	0-24000RPM	
	Motor and Driver	JMC stepper motor driver 860H+motor 450B+Patent reducer	
	Inverter	BEST inverter	
	Table surface	T-slot table	
	Lubrication system	Manual lubrication system	
	Calibration	Tool sensor	
	Transmission	XZ axis by Taiwan PMI 20 rail guide,Y axis by Taiwan PMI 25 rail guide。 XY axis with J&T 1.25M helical rack,Z axis with Taiwan TBI ball screw。 Whole machine reducer 1:5。	
	Portable control box, place the position saving device to take up space.		
	200x300mm square pipe welding bed structure.		
	Nc center precision machining T6 material precision machine head accessories set.		
Y-axis double protection anti-dust optimization design,better protection of linear guide service life.			

	The equipment is equipped with a professional forklift station to facilitate loading and unloading equipment.
	Humanized mechanical structure design, optimized product packaging method to save transportation cost.
Delivery time	About 7-10 working days after get deposit
Warranty Time	One year for the whole machine.
Packing size	3060mm*2060mm*1350mm, 8.5CBM, 950KG

